

Retail-Pos^{pro}



- Low-Power High Performance Intel Celeron J1900 Quad Core Processor
 - Sleek and Compact Body with Small Foot Print
- 15" Bezel-Free True -Flat Display with PCAP Touch
 - LED Back Light Delivering Bright and Crisp Images
- Multiple I/O Interfaces for Peripherals
 - Flexible Installation on a Counter and wall
 - Faster Installation and Serviceability
- Engineered Optimized for Hospitality and Retail Business



Features & Benefits



New Look - New Design
Sleek & Compact. Small Foot Print
Modern & Contemporary Styling



Powerful Performer
Intel Celeron J1900 Quad Core Processor
Low Power. High Performance F/L processor.




Superior Touch Display
15" Bezel Free True Flat LCD
PCAP Touch. LED Backlight



Install It Anywhere
On a Counter or a wall
VESA Compatible (Option)



Save Time & Cost
Easy Access to I/O Interfaces
Faster Installation & Serviceability



Connect It to All
Multiple I/O Interfaces
6 USB. 5 Serial. Optional Expansion Available

Specifications

Retail-Pos®

SYSTEM INFO

Processor	Intel® Celeron™ J1900 (2.0GHz) Quad Core Processor, Fanless
Chipset	Intel® Bay Trail
Memory	4GB Standard, up to 8GB DDR3L 1600 MT/s, Socket 1 x DIMM
Storage	SATA 2 (3Gb/s) 2.5 inch SSD 64GB, Support AHCI
OS	Windows7, Windows 8.1, Windows 10 to IoT Enterprise, POS Ready 7
Audio	Realtek ALC 662-VD

DISPLAY

Type	15" TFT LCD, LED Backlight
Resolution	1024 x 768
Brightness	300cd/m ² (typ)
Touch screen	Projective Capacitive Touch

Interface

Display	1 x VGA (with Power Output)
USB	6 (Rear 2, Back 4, USB 2.0x 6) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45
Serial	5 (Com 1 with 5V /12V Power Output on 9pins, BIOS, (Com 2-3 RJ 45, Full Signal) (Com 4 -RJ 11, only TX/RX, 12V Power Output, Reserved for CDP) (Com 5 Reserved for Cash Drawer Port) (Com 6 R RJ-45, Only
LAN	1 x Gigabit Ethernet, RJ 45
Audio	1 x Lineout
Power DC IN	1 x (4 Pin Connector)

Power

Power Supply	Adaptor 12V / 5A
--------------	------------------

Physical & Environmental

Dimension (W x H x D)	364 x 333 x 210 (mm) 14.3 x 13.1 x 8.2 (inch)
Certification	CE, FCC, KC, CB, CCC
Net Weight	5.3Kg
Operation Temp	0°C-60° at 10% to 90% Humidity

Options & Peripherals

2nd Display	9.7", 12.1", 15" LCD Display, 1024 x 768 (Optional Touch Screen)
Customer Display	VFD, 20 Columns x 2 Lines
I/O Expansion	1 x com5 (RJ-45 8 Pins) (Factory Option) 1 x Cash Drawer Port (Factory Option)
Storage	2.5 Inch SSD 128 GB, HDD - 500 GB, 1TB
MSR	Comply with ISO 7811, Support 1 -2 -3 Track
Smart Card Reader	EMV Level 1,2
Dallas / Finger Print	Dallas i-Button Reader, Finger Print Yes
Wall Mount Kit	VESA-Compatible, 75 x 75 (mm) 100 x 100 (mm)
Serial Conversion Cable	RJ 45 to D-Sub 9
Speaker	2 x 0.8W (Stereo) (Factory Option)