

Retail-Pos^{pro}



Save Time & Cost
Easy Access to I/O Interfaces
Faster Installation & Serviceability



Powerful Performer
Intel Core i5 - 6200U Processor
Low Power. High Performance Fanless



Connect It to All
Multiple I/O Interfaces
6 USB. 5 Serial.
Optional Expansion Available



New Look - New Design
Sleek & Compact. Small Foot Print
Modern & Contemporary Styling



Superior Touch Display
15" Bezel Free True Flat LCD
PCAP Touch. LED Backlight



Install It Anywhere
On a Counter or a wall
VESA Compatible (Option)

Retail-Pos[®]

SYSTEM

Processor	Intel Core i5 -6200U Processor(3M Cache, 2.80 GHz)
Chipset	ITE Tech IT8786E
Memory	4GB Standard, DDR4L 2133 MT/s, Socket 1 x SODIMM (Max. 16GB)
Storage	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
OS	Windows 7, Windows 8.1, Windows 10 IoT Enterprise, POS Ready 7
Audio	Realtek ALC662-VD

DISPLAY

Type	15" TFT LCD, LED Backlight
Resolution	1024 x 768
Brightness	300 cd/m ² (typ.)
Touch screen	Projective Capacitive Touch

INTERFACE

Display	1 x VGA (With Power Output)
USB	6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45
Serial	5 (COM 1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2~3 RJ-45 , Full Signal) (COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved for CDP) (COM5 Reserved for Cash Drawer Port) (COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR)
Power DC-IN	1 x (3 Pin Connector)
LAN	1 x Gigabit Ethernet, RJ-45
Audio	1 x Line-out
Extension Slot	mini PCIe, m-SATA

POWER

Power Supply	Adaptor 24V, 2A 24V, 4A(Powered USB Option)
--------------	---

OPTIONS & PERIPHERALS

2nd Display	9.7", 12.1", 15" LCD Display, 1024 x 768, Optional Touch screen
Customer Display	VFD, 20 Columns x 2 Lines
I/O Expansion	1 x COM5 (RJ-45 8 Pins) (Factory Option) 1 x Cash Drawer Port (Factory Option) 1 x Powered USB (24V)
Storage	2.5 inch SSD 128GB, HDD 500GB, 1TB
MSR	Comply with ISO 7811, Support 1 & 2 & 3 Track
Smart Card Reader	EMV Level 1, 2
Dallas	Dallas i-button Reader

Fingerprint	Yes
Camera	5M USB Interface (Internal) (Factory Option)
Wall Mount Kit	VESA-Compatible, 75 x 75(mm), 100 x 100(mm)
Serial Conversion	RJ-45 to D-sub 9 Cable
Speaker	2 x 0.8W (Stereo)
Wi Fi	Mini PCIe for Wireless LAN

PHYSICAL & ENVIRONMENTAL

Operating Temperature	0°C ~ 60°C at 10% to 90% Humidity
Storage Temperature	-20°C ~ 80°C at 10% to 90% Humidity
Dimensions	(W x H x D) 364 x 333 x 210(mm), 14.3 x 13.1 x 8.2(in)
Packing Dimensions	(W x H x D) 500 x 470 x 300(mm), 19.6 x 18.5 x 11.8(in)
Net Weight	5,300g, 11.6lbs
Packing Weight	8,000g, 17.6lbs
Certification	CE, FCC, KC, CB, CCC
Colour	Matt Dark Grey, High Gloss White

Peripheral Options



Customer Display
• VFD (2 Lines x 20 Characters)





2nd Display
• 9.7", 12.1", 15" LCD



Multi-Reader
• MSR, SCR

Dimension View



PSPL/HO/RP_PLS/i5/10-2017

Retail-Pos®

POS SOLUTIONS
Private Limited

POS SOLUTIONS PVT LTD
306, 3rd floor, Sanjar Enclave,
S.V. Road, Kandivali (W)
Mumbai - 400 067. India.
Email: sales@pos-india.com
Web: www.pos-india.com

Your Local Dealer

Mumbai - Chennai - Delhi - Bengaluru - Hyderabad - Kochi - Pune - Coimbatore
Ahmedabad - Jaipur - Lucknow - Patna - Kolkata